

LUXASCOPE AURIS SET LED 2.5 V, WHITE (OTOSCOPE + OPHTHALMOSCOPE)

LUXAMED®

Ref. AF.416.914

Complete set for precision diagnosis: Auris LED 2.5V white otoscope + LuxaScope LED 2.5V white ophthalmoscope

Description

Otoscope :

Lighting: LED ring with 6 LEDs (concentric),

no fibre optics, the field of vision is not limited.

- Maintenance-free, as no bulb change is required.

- Possibility of varying brightness intensity.

- Automatic switch-off after 3 minutes

- LED life: approx. 100,000 hours at constant current

current

- Illuminance: approx. 10,000 Lux

- Colour temperature: approx. 4,200 K

- Optimised head design

- Swivelling magnifier, 3x magnification

- Injection port for pneumatic test

- Handle made from two materials: aluminium and fibreglass

fibreglass, compatible with the head of the Lux dermatoscope and

LuxaScope ophthalmoscope head

- ON/OFF push-button switch

- Power supply: 2x AAA alkaline batteries, included

- Includes 20 grey disposable specula, 10 of which are 2.5mm and 10 of which are

4.0mm specula

LUXASCOPE AURIS SET LED 2.5 V, WHITE (OTOSCOPE + OPHTHALMOSCOPE)

LUXAMED®

Ref. AF.416.914

Ophthalmoscope :

- Correction values: + 20 bis - 20 D ($\pm$ 1 2 3 4 6 8 10 15 20 D)
 - 5 different filters available: large spot, small spot, green filter, half-moon and reticle
 - Illumination: LED
 - Brightness can be dimmed to avoid glare glare
 - Automatic switch-off after 3 minutes
 - LED life: approx. 50,000 hours at constant current current
 - Colour temperature: approx. 4,200 K
 - Optimised head design
 - Handle made from two materials: aluminium and fibreglass reinforced, compatible with otoscope and dermatoscope heads
- LuxaScope LED
- ON/OFF push-button switch
 - Includes 2 AAA alkaline batteries

LUXASCOPE AURIS SET LED 2.5 V, WHITE (OTOSCOPE + OPHTHALMOSCOPE)

LUXAMED®

Ref. AF.416.914

Features

CE Marking	CE	Medical device	Class I
Bar code	04260381964445	Warranty (months)	24
Country	Germany		

DIMENSIONS AND WEIGHT

Packed unit / Width (cm)	nc	Packed unit / Height (cm)	nc
Packed unit / Length (cm)	nc	Packed unit / Weight	nc

SPECIFIC STORAGE CONDITIONS

Minimum temperature	-10	Max temperature	45
Minimum humidity	10	Maximum humidity	90

OTHER FEATURES