

LUXASCOPE AURIS SET LED 3.7 V, WHITE (OTOSCOPE + OPHTHALMOSCOPE)

Ref. AF.426.914

LUXAMED®



CE



Complete rechargeable set for precision diagnosis: Auris LED 3.7V black otoscope + LuxaScope LED 3.7V black ophthalmoscope

Description

08/10/2025 01:45:23 – For information purposes only, can be subject to change

LUXASCOPE AURIS SET LED 3.7 V, WHITE (OTOSCOPE + OPHTHALMOSCOPE)

LUXAMED®

Ref. AF.426.914

Otoscope :

Lighting: LED ring with 6 LEDs (concentric),

no fibre optics, the field of vision is not limited.

- Maintenance-free, as no bulb change is required
- Possibility of varying brightness intensity
- Automatic switch-off after 3 minutes
- LED life: approx. 100,000 hours at constant current
- Illuminance: approx. 10,000 Lux
- Colour temperature: approx. 4,200 K
- Optimised head design
- Swivelling magnifier, 3x magnification
- Injection port for pneumatic test
- Handle made from two materials: aluminium and fibreglass

reinforced, compatible with dermatoscope head and ophthalmoscope

LuxaScope LED

- ON/OFF push-button switch
- Power supply: 2x AAA alkaline batteries, included
- Includes 20 grey disposable specula (10 x 2.5mm and 10 x 4.0mm)

Ophtalmoscope :

Correction values: + 20 bis - 20 D ($\pm$ 1 2 3 4 6 8 10 15 20 D)

- 5 different filters available: large spot, small spot, green filter, half-moon and reticle
- Illumination: LED
- Brightness can be dimmed to avoid glare
- Automatic switch-off after 3 minutes
- LED life: approx. 50,000 hours at constant current

LUXASCOPE AURIS SET LED 3.7 V, WHITE (OTOSCOPE + OPHTHALMOSCOPE)

LUXAMED®

Ref. AF.426.914

- Colour temperature: approx. 4,200 K
 - Optimised head design
 - Handle made from two materials: aluminium and fibreglass reinforced, compatible with otoscope and dermatoscope heads
- LuxaScope LED

Features

CE Marking	CE	Medical device	Class I
Bar code	04260381964513	HS Code	9018908400
Warranty (months)	24	Country	Germany

DIMENSIONS AND WEIGHT

Packed unit / Width (cm)	nc	Packed unit / Height (cm)	nc
Packed unit / Length (cm)	nc	Packed unit / Weight	nc

SPECIFIC STORAGE CONDITIONS

Minimum temperature	-10	Max temperature	45
Minimum humidity	10	Maximum humidity	90

OTHER FEATURES