



Ref. BCASPI56















Ref. BCASPI56

Description

with foot control and communicating jars

Designed to drain the patient's body fluids, gases, tissues and bones, during or after a procedure. The state-of-the-art oil-fre pump system guarantees excellent suction capabilities and maximum vacuum pressure in seconds, without any need for maintenance.

- The precise dashboard and the full range of accessories that come with it make it the ideal device for surgical aspiration and liposuction.
- Available in 3 versions: Basic, FS or full
 Accessories for the Basic version: Fluid collection jar with an anti-reflux valve

8x14 Silicone hoses (autoclavable) and conical connectors ø 10-11-12mm

Antibacterial & hydrophobic filter (single patient)

Power cord with Schuko

plug• Accessories for the FS version:

Fluid collection jar with an anti-reflux

valve- 8x14 Silicone hoses (autoclavable) and conical connectors ø 10-11-12mm- Antibacterial & hydrophobic filter (single patient)

Power cord with Schuko plug

Pedal

· Accessories for the Full version:

Fluid collection jar with an anti-reflux valve

13/10/2025 21:52:46 – For information purposes only, can be subject to change





Ref. BCASPI56

8x14 Silicone hoses (autoclavable) and conical connectors ø 10-11-12mm

- Antibacterial & hydrophobic filter (single patient)
- Power cord with Schuko plug,

Pedal

Electronic Transfer System between collection jars

Technical characteristics

:- Engine: Oil-free piston pump requiring no maintenance

Power supply: 230V-50Hz

Maximum vacuum (adjustable): 0.90 Bar -90 kPa -675 mmHg

Max free air flow: 90 l/min

Noise level: 46.4 dBA

Weight: 20 kg

- Dimensions: 46 x 85 x 42 cm



13/10/2025 21:52:46 – For information purposes only, can be subject to change





Ref. BCASPI56

Features

CE Marking	CE0123	Medical device	Class lla
Bar code	3661040139425	HS Code	90189084
Warranty (months)	24	Country	Italy
DIMENSIONS AND WEIGHT			
Packed unit / Width (cm)	50	Packed unit / Height (cm)	92
Packed unit / Length (cm)	50	Packed unit / Weight	21
SPECIFIC STORAGE CONDITIONS			
Minimum temperature	-20	Max temperature	45
Minimum humidity	NA	Maximum humidity	85
OTHER FEATURES			
Packed unit / Quantity	1		