

CARDIOMATE PC ECG BLUETOOTH SPENGLER

Ref. 260040



CE
0123



19/06/2026 08:02:19 – For information purposes only, can be subject to change

CARDIOMATE PC ECG BLUETOOTH SPENGLER

Ref. 260040



A SPENVEL BLUETOOTH PC-ECG with XXL performance in the palm of your hand

Description

Wireless digital ECG, the Cardiomate PC bluetooth allows the real-time display of a 12-lead ECG on the screen of a computer or Android tablet and its printing on an A4 printer.

Compatible with Windows and Android system, the Cardiomate PC Bluetooth connects using Bluetooth technology (or USB).

With the same performance as the Cardiomate range and with its compact and lightweight housing, the Cardiomate PC Bluetooth is a state-of-the-art measuring instrument in the office or on the go.

The software allows the visualization, recording, analysis and storage of ECGs in a clear and intuitive way. The wireless connection is functional up to 15m.

HIGH MEASUREMENTS ACCURACY :

- Visualization of the 12 leads in real time on PC
- Sampling rate: 32,000Hz
- 24 bit converter
- Automatic interpretation and calculation of intervals
- Pacemaker detection

EASY TO USE

- Connection to PC or Android tablet / Smartphone by bluetooth (USB only on PC)
- Power supply by 2 AA batteries, self-powered USB
- Simple and intuitive PC and Android software
- PC software compatible with other Cardiomate ECG.

COMPACT AND LIGHT

- Dimensions: 68x126x24mm
- Weight: 132g (with batteries)

CARDIOMATE PC ECG BLUETOOTH SPENGLER

Ref. 260040



Features

CE Marking	CE0123	Medical device	Class IIa
Bar code	3700446042066	HS Code	9018110000
Warranty (months)	24	Country	China
DIMENSIONS AND WEIGHT			
Packed unit / Width (cm)	nc	Bare Unit / Width (cm)	6.7
Packed unit / Height (cm)	nc	Bare Unit / Height (cm)	2.4
Packed unit / Length (cm)	nc	Bare Unit / Length (cm)	12.6
Packed unit / Weight	nc	Bare Unit / Weight (kg)	0.132
SPECIFIC STORAGE CONDITIONS			
Minimum temperature	NA	Max temperature	NA
Minimum humidity	NA	Maximum humidity	NA
OTHER FEATURES			
Packed unit / Quantity	1		